

Manipulations for delivering HIF beams onto targets: (1) Smoothing by arc wobblers, (2) Differential acceleration in final beam lines

Thursday, 16 August 2012 14:35 (2h 40m)

A. Friedman

LLNL, Livermore CA 94550 USA

and

Heavy Ion Fusion Science Virtual National Laboratory

We describe two techniques related to the delivery of the ion beams onto the target in a Heavy Ion Fusion power plant.

(1) By manipulating a set of ion beams upstream of a target, it is possible to achieve a more uniform energy deposition pattern. We consider an approach to deposition smoothing that is based on rapidly “wobbling” each of the beams back and forth along a short arc-shaped path, via oscillating fields applied upstream of the final pulse compression [A. Friedman, *Phys. Plasmas* 19, 063111 (2012)]. Uniformity is achieved in the time-averaged sense; the oscillation period must be sufficiently shorter than the target’s hydrodynamic response timescale. This work builds on two earlier concepts: elliptical beams [D. A. Callahan and M. Tabak, *Phys. Plasmas* 7, 2083 (2000)]; and beams wobbled through full-circle rotations [e.g., R. C. Arnold, et al., *Nucl. Instr. and Meth. A* 199, 557 (1982)]. Arc-based smoothing remains usable when the geometry precludes full-circle wobbling, e.g., for the X-target [E. Henestroza, B. G. Logan, and L. J. Perkins, *Phys. Plasmas* 18, 032702 (2011)] and some distributed-radiator targets.

(2) By accelerating some beams “sooner” and others “later,” it is possible to simplify the beam line configuration in a number of cases. For example, the time delay between the “foot” and “main” pulses can be generated without resorting to large arcs in the main-pulse beam lines. This may minimize beam bending, known to be a source of emittance growth in space-charge-dominated beams. It is also possible to arrange for the simultaneous arrival on target of a set of beams (e.g., for the foot-pulse) without requiring that their path lengths be equal. This may ease a long-standing challenge in designing a power plant, in which the tens or hundreds of beams entering the chamber all need to be routed from one or two multi-beam accelerators or transport lines.

Work performed under auspices of U.S. DoE by LLNL under Contract DE-AC52-07NA27344.

Primary author: FRIEDMAN, Alex (LBNL)

Presenter: FRIEDMAN, Alex (LBNL)

Session Classification: Poster session