



**U.S. MAGNET  
DEVELOPMENT  
PROGRAM**

# CCT Progress Update

Diego Arbelaez, Lucas Brouwer, Shlomo Caspi, Dan Dietderich, Ray Hafalia, Scott Myers, Thomas Lipton, Maxim Marchevsky, Matt Reynolds, James Swanson, Marcos Turqueti, Xiaorong Wang, Soren Prestemon, Stephen Gourlay

07/12/2017



- **Basic Parameters**
- **Fabrication**
- **Instrumentation**
- **Test Plan**




# CCT 3/4 Parameters

- Tested and planned CCT 2-layer series has nearly identical geometry
  - 90 mm diameter inner bore
  - 1 m physical length
  - Mandrel grooves for ~10 mm wide and ~1.4 mm thick cable

## Magnet Parameters

	<b>CCT3/4</b>
	Nb <sub>3</sub> Sn
Conductor	RRP 54/61
Cu:SC ratio	0.85
Inner Bore Diameter [mm]	90
Cable Width [mm]	10.1
Cable Thickness [mm]	1.4
Number of Strands	23
Cable Insulation	S-glass Braid 0.2 mm thick
Iron Yoke	Yes
Impregnation Material	CTD-101K
Short Sample Current [kA]	18.3
Short Sample Bore Field [T]	9.9

## Magnet Load Line for CCT4





# 2-Layer CCT Nb<sub>3</sub>Sn Plan (CCT Technology Development)


	CCT3	CCT4
Bore size [mm]	90	90
Groove design	constant width	1.25 mm gap at pole
Conductor	RRP 54/61 Ta doped	RRP 54/61 Ta doped
HT Temp [C]	650	660
Potting configuration	full magnet	full magnet
Epoxy	CTD-101K	CTD-101K
Layer-to-layer interface	bonded	mold released



# CCT4 Mandrels and Winding

- CCT 4 Mandrels have 1.25 mm gap at the pole for cable expansion
- Other features are the same as CCT3
- Cable is wound against the inner surface of the turn at the pole
- Resistance to mandrel  $> 5 \text{ k}\Omega$ 
  - Wider groove by 0.1 mm
  - Extra space at the pole

Pole Gaps



Lead End







# CCT4 – Heat Treatment

- Copper wire was inserted into groove to force the cable to the bottom of the channel (same as 10-turn tests)
- Mandrel is wrapped with hose clamps
- Cable stays in channel after heat treatment
- Mandrels distort 0.5 – 1 mm after heat treatment in the N/S orientation
  - Not yet clear how much influence cable has on distortion as opposed to machining stress
  - May require additional annealing step after grooves are machined to avoid distortions


CCT4 Heat Treatment Configuration



Cable Position After Heat Treatment of CCT4



Mandrel Distortion After Heat Treatment








# CCT4 – Coil Preparation

- Glass fiber mat used to fill remaining space in channels
- $\text{Nb}_3\text{Sn}$  cable spliced with two NbTi lead cables in machined channel
- Voltage taps were soldered at the pole locations using flexible Kapton PCB


Glass Reinforcement



Lead Splice





Voltage Tap Connections





# CCT4 – Assembly

- Layers are wrapped with G10 sheet before assembly
- Assembly of layer 1 / layer 2 was difficult due to amount of mandrel distortion
- Cable is protected by mandrel since it is below the surface









# CCT4 – Epoxy Impregnation




- Mold release applied between layers
- Two layers and shell impregnated together
- Heaters placed inside the bore and on the shell surface





# Test Preparation

- Layer-to-Layer splices were completed
- Voltage tap wires were added and secured
- Acoustic sensors were installed and tested
- Iron yoke was assembled







- Voltage taps
- Acoustic Sensors on Shell
- Strain gages on Shell (Pole and Midplane)
- Spot Heater and Thermometer in Groove


Spot Heater



Strain Gages




Acoustic Sensors





# Voltage Tap Layout





- **Installation and electrical checks (5-7 days) (75 % complete)**
- **Cooldown and system checks (3-4 days – projected to start July 16)**
- **First magnet current cycle (1 day)**
- **Quench training (~3-4 days)**
- **Magnetic measurements (1-2 days)**
- **Magnetic measurements (1-2 days)**